

Features

- 2625 Watts Peak Power ($t_p = 8/20\mu s$)
- Working Voltage: 22V
- Solid-state technology
- Low clamping voltage: 35V Maximum at IPP = 75A ($t_p = 8/20\mu s$)

IEC COMPATIBILITY (EN61000-4)

- IEC 61000-4-2 (ESD) $\pm 30kV$ (air), $\pm 30kV$ (contact)
- IEC 61000-4-4 (EFT) 40A (5/50ns)
- IEC 61000-4-5 (Lightning) 75A (8/20 μs)


Mechanical Characteristics

- DFN2020-6L package
- Marking : Making Code
- Packaging : Tape and Reel per EIA 481
- RoHS Compliant & HF
- Device meets MSL1 requirement

Applications


- USB Type-C
- VBUS Lines
- Industrial Sensors
- Notebooks and Tablets
- Storage Devices

Functional Diagram



Pin Configuration

WS8119YK6 is in a 2 x 2mm, 6-pin DFN package. The input or connection to the protected bus is made at pins 4, 5, and 6. Ground connection is made at pins 1, 2, and 3. The exposed center pad may optionally be connected to GND.




Pin Number	Pin Name	Description
1,2,3	GND	Ground
4,5,6	IN	EOS and ESD Protection Input
Center Pad	GND	Optional GND connection

Absolute Maximum Rating

Rating	Symbol	Value	Units
Peak Pulse Power ($t_p = 8/20\mu s$)	P_{PP}	2625	Watts
Peak Pulse Current ($t_p = 8/20\mu s$)	I_{PP}	75	A
Human Body Model	HBM	8000	V
Operating Temperature	T_J	-55 to + 125	°C
Storage Temperature	T_{STG}	-55 to +150	°C

Electrical Parameters

Symbol	Parameter
I_{PP}	Reverse Peak Pulse Current
V_C	Clamping Voltage @ I_{PP}
V_{RWM}	Reverse Stand-Off Voltage
I_R	Reverse Leakage Current @ V_{RWM}
V_{BR}	Breakdown Voltage @ I_T
I_T	Test Current
I_F	Forward Current
V_F	Forward Voltage @ I_F



Electrical Characteristics(T=25°C unless otherwise noted)

WS8119YK6						
Parameter	Symbol	Conditions	Minimum	Typical	Maximum	Units
Reverse Stand-Off Voltage	V_{RWM}				22	V
Reverse Breakdown Voltage	V_{BR}	$I_T=1mA$	24			V
Reverse Leakage Current	I_R	$V_{RWM}=22V$			500	nA
Forward Voltage	V_F	$I_F=1mA$	0.25	0.54	0.65	V
Clamping Voltage ¹	V_C	$I_{PP}=40A, t_p=8/20\mu s$			30	V
Clamping Voltage ¹	V_C	$I_{PP}=75A, t_p=8/20\mu s$		29.5	35	V
Junction Capacitance	C_j	$V_R=0V, f=1MHz$		560	700	pF

Note: 1.Measured from pin 4 & pin 5 & pin6 to pin 1& pin 2& pin3;

Typical Characteristics

Figure 1: Peak Pulse Power vs. Pulse Time




Figure 2: Power Derating Curve




Figure 3: Clamping Voltage vs. Peak Pulse Current




Figure 4: Normalized Junction Capacitance vs. Reverse Voltage




Figure 5: Clamping Voltage (tp=8/20, Ipp=40A)






Figure 6: Clamping Voltage (tp=8/20, Ipp=75A)




Soldering Parameters

Reflow Condition		Pb – Free assembly
Pre Heat	Temperature Min ($T_{s(min)}$)	150°C
	Temperature Max ($T_{s(max)}$)	200°C
	Time (min to max) (t_s)	60 – 190 secs
Average ramp up rate (Liquidus Temp) (T_L) to peak		5°C/second max
$T_{s(max)}$ to T_L —Ramp-up Rate		5°C/second max
Reflow	Temperature (T_L) (Liquidus)	217°C
	Temperature (t_L)	60 – 150 seconds
Peak Temperature (T_P)		260+0/-5 °C
Time within actual peak Temperature (t_p)		20 – 40 seconds
Ramp-down Rate		5°C/second max
Time 25°C to peak Temperature (T_P)		8 minutes Max.
Do not exceed		280°C




Tape And Reel Information


Reel Dimensions



Tape Dimensions



Quadrant Assignments For PIN1 Orientation In Tape



RD	Reel Dimensions	7 inch
W	Overall width of the carrier tape	8 mm
P1	Pitch between successive cavity centers	4mm

Outline Drawing –DFN2020-6L

PACKAGE OUTLINE

TOP VIEW

BOTTOM VIEW

SIDE VIEW

DFN2020-6L

SYMBOL	MILLIMETERS	
	MIN	MAX
A	0.500	0.600
A1	0.025	0.075
D	1.900	2.100
E	1.900	2.100
D1	1.500	1.700
E1	0.900	1.100
b	0.250	0.350
L	0.185	0.245
L1	0.035REF	
L2	0.200REF	
k	0.250REF	
h	0.200REF	
e	0.650BSC	

DIMENSIONS	
DIM	MILLIMETERS
C	1.95
K	1.0
P	0.65
X	0.30
Y	0.45
D	1.6

Notes

- Dimensioning and tolerances per ANSI Y14.5M, 1985.
- Controlling Dimension: Inches
- Dimensions are exclusive of mold flash and metal burrs.

Marking Codes

Part Number	Marking Code
WS8119YK6	<p style="font-size: small; color: red;">基岛斜角位置 (此圆点为打印内容) Pnt1</p> <p style="font-size: x-small;">8YK6=Specific Device Code XXXX=Lot Code</p>

Package Information

Qty: 3k/Reel

CONTACT INFORMATION

No.1001, Shiwan (7) Road, Pudong District, Shanghai, P.R.China.201207

Tel: 86-21-50310888 Fax: 86-21-50757680 Email: market@way-on.com

WAYON website: <http://www.way-on.com>

For additional information, please contact your local Sales Representative.

WAYON ® is registered trademark of WAYON Corporation.

Product Specification Statement

1. The product specification aims to provide users with a reference regarding various product parameters, performance, and usage. It presents certain aspects of the product's performance in graphical form and is intended solely for users to select product and make product comparisons, enabling users to better understand and evaluate the characteristics and advantages of the product. It does not constitute any commitment, warranty, or guarantee.
2. The product parameters described in the product specification are numerical values, characteristics, and functions obtained through actual testing or theoretical calculations of the product in an independent or ideal state. Due to the complexity of product applications and variations in test conditions and equipment, there may be slight fluctuations in parameter test values. WAYON shall not guarantee that the actual performance of the product when installed in the customer's system or equipment will be entirely consistent with the product specification, especially concerning dynamic parameters. It is recommended that users consult with professionals for product selection and system design. Users should also thoroughly validate and assess whether the actual parameters and performance when installed in their respective systems or equipment meet their requirements or expectations. Additionally, users should exercise caution in verifying product compatibility issues, and WAYON assumes no responsibility for the application of the product.
3. WAYON strives to provide accurate and up-to-date information to the best of our ability. However, due to technical, human, or other reasons, WAYON cannot guarantee that the information provided in the product specification is entirely accurate and error-free. WAYON shall not be held responsible for any losses or damages resulting from the use or reliance on any information in these product specifications. WAYON reserves the right to revise or update the product specification and the products at any time without prior notice, and the user's continued use of the product specification is considered an acceptance of these revisions and updates. Prior to purchasing and using the product, users should verify the above information with WAYON to ensure that the product specification is the most current, effective, and complete. If users are particularly concerned about product parameters, please consult WAYON in detail or request relevant product test reports. Any data not explicitly mentioned in the product specification shall be subject to separate agreement.
4. Users are advised to pay attention to the parameter limit values specified in the product specification and maintain a certain margin in design or application to ensure that the product does not exceed the parameter limit values defined in the product specification. This precaution should be taken to avoid exceeding one or more of the limit values, which may result in permanent irreversible damage to the product, ultimately affecting the quality and reliability of the system or equipment.
5. The design of the product is intended to meet civilian needs and is not guaranteed for use in harsh environments or precision equipment. It is not recommended for use in systems or equipment such as medical devices, aircraft, nuclear power, and similar systems, where failures in these systems or equipment could reasonably be expected to result in personal injury. WAYON shall assume no responsibility for any consequences resulting from such usage.
6. Users should also comply with relevant laws, regulations, policies, and standards when using the product specification. Users are responsible for the risks and liabilities arising from the use of the product specification and must ensure that it is not used for illegal purposes. Additionally, users should respect the intellectual property rights related to the product specification and refrain from infringing upon any third-party legal rights. WAYON shall assume no responsibility for any disputes or controversies arising from the above-mentioned issues in any form.