



80V N-Channel Enhancement Mode Power MOSFET

Description

WMB060N08HG2 uses Wayon's 2nd generation power trench MOSFET technology that has been especially tailored to minimize the on-state resistance and yet maintain superior switching performance. This device is well suited for high efficiency fast switching applications.

**Features**

- $V_{DS} = 80V$, $I_D = 82A$
- $R_{DS(on)} < 6m\Omega$ @ $V_{GS} = 10V$
- Green Device Available
- 100% EAS Guaranteed
- Low $R_{DS(ON)}$
- High Speed Power Switching

**Applications**

- Synchronous Rectification in SMPS
- DC/DC Conversion
- Hard Switching and High Speed Circuit

Absolute Maximum Ratings ($T_A = 25^\circ C$, unless otherwise noted)

Parameter	Symbol	Value	Unit
Drain-Source voltage	V_{DS}	80	V
Gate-Source voltage	V_{GS}	± 20	V
Continuous Drain Current $T_c=25^\circ C$	I_D	82	A
		50	
Pulsed Drain Current ¹	I_{DM}	328	A
Single Pulse Avalanche Energy ²	EAS	125	mJ
Total Power Dissipation	P_D	75	W
Operating Junction and Storage Temperature Range	T_J , T_{STG}	-55 to 150	°C

Thermal Characteristics

Parameter	Symbol	Value	Unit
Thermal Resistance from Junction-to-Ambient ³	$R_{\theta JA}$	49.5	°C/W
Thermal Resistance from Junction-to-Case	$R_{\theta JC}$	1.72	°C/W

Electrical Characteristics ($T_J = 25^\circ\text{C}$, unless otherwise noted)

Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit
Static Characteristics						
Drain-Source Breakdown Voltage	$V_{(\text{BR})\text{DSS}}$	$V_{GS} = 0V, I_D = 250\mu\text{A}$	80	-	-	V
Gate-body Leakage Current	I_{GSS}	$V_{DS} = 0V, V_{GS} = \pm 20V$	-	-	± 100	nA
Zero Gate Voltage Drain Current $T_J=25^\circ\text{C}$	I_{BSS}	$V_{DS} = 80V, V_{GS} = 0V$	-	-	1	μA
			-	-	100	
Gate-Threshold Voltage	$V_{GS(\text{th})}$	$V_{DS} = V_{GS}, I_D = 250\mu\text{A}$	2	3	4	V
Drain-Source On-Resistance ⁴	$R_{DS(\text{on})}$	$V_{GS} = 10V, I_D = 20A$	-	5.2	6	$\text{m}\Omega$
Forward Transconductance ⁴	g_{fs}	$V_{DS} = 10V, I_D = 20A$	-	49	-	S
Dynamic Characteristics⁵						
Input Capacitance	C_{iss}	$V_{DS} = 40V, V_{GS} = 0V, f = 1\text{MHz}$	-	2422	-	pF
Output Capacitance	C_{oss}		-	428	-	
Reverse Transfer Capacitance	C_{rss}		-	15	-	
Gate Resistance	R_g	f = 1MHz	-	1.35	-	Ω
Switching Characteristics⁵						
Total Gate Charge	Q_g	$V_{GS} = 10V, V_{DS} = 40V, I_D = 20A$	-	41	-	nC
Gate-Source Charge	Q_{gs}		-	7.8	-	
Gate-Drain Charge	Q_{gd}		-	11.5	-	
Turn-On Delay Time	$t_{d(on)}$	$V_{GS} = 10V, V_{DD} = 40V, R_G = 3\Omega, I_D = 20A$	-	10.5	-	ns
Rise Time	t_r		-	7	-	
Turn-Off Delay Time	$t_{d(off)}$		-	24.6	-	
Fall Time	t_f		-	8.8	-	
Reverse Recovery Time	t_{rr}	$I_F = 20A, dI/dt = 100A/\mu\text{s}$	-	42	-	ns
Reverse Recovery Charge	Q_{rr}		-	59	-	nC
Drain-Source Body Diode Characteristics						
Diode Forward Voltage ⁴	V_{SD}	$I_S = 20A, V_{GS} = 0V$	-	-	1.2	V
Continuous Source Current	$T_c = 25^\circ\text{C}$	I_S	-	-	82	A

Notes:

1. Repetitive rating, pulse width limited by junction temperature $T_{J(\text{MAX})}=150^\circ\text{C}$
2. The test condition is $V_{DD}=25V, V_{GS}=10V, L=0.4\text{mH}, I_{AS}=25A$.
3. The data tested by surface mounted on a 1 inch² FR-4 board with 2OZ copper, The value in any given application depends on the user's specific board design.
4. The data tested by pulsed, pulse width $\leq 300\mu\text{s}$, duty cycle $\leq 2\%$.
5. This value is guaranteed by design hence it is not included in the production test.

Typical Characteristics




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics







Figure 3. Forward Characteristics of Reverse

Figure 4. $R_{DS(ON)}$ vs. V_{GS} Figure 5. $R_{DS(ON)}$ vs. I_D Figure 6. Normalized $R_{DS(on)}$ vs. Temperature




Figure 7. Capacitance Characteristics




Figure 8. Gate Charge Characteristics




Figure 9. Power Dissipation




Figure 10. Safe Operating Area










Figure 11. Normalized Maximum Transient Thermal Impedance

Test Circuit**Figure A. Gate Charge Test Circuit & Waveforms****Figure B. Switching Test Circuit & Waveforms****Figure C. Unclamped Inductive Switching Circuit & Waveforms**

Mechanical Dimensions for PDFN5060-8L

COMMON DIMENSIONS


SYMBOL	MM	
	MIN	MAX
A	0.90	1.20
A3	0.15	0.35
D	4.80	5.40
E	5.90	6.35
D1	3.61	4.31
E1	3.30	3.92
E2	5.50	6.06
k	1.10	-
b	0.30	0.51
e	1.27BSC	
L	0.38	0.71
L1	0.05	0.36
H	0.38	0.71
θ	0°	12°



Ordering Information

Part	Package	Marking	Packing method
WMB060N08HG2	PDFN5060-8L	B060N08H	Tape and Reel

Marking Information



B060N08H = Device code
WWXX XXX= Date code

Contact Information

No.1001, Shiwan(7) Road, Pudong District, Shanghai, P.R.China.201207

Tel: 86-21-50310888 Fax: 86-21-50757680 Email: market@way-on.com

WAYON website: <http://www.way-on.com>

For additional information, please contact your local Sales Representative.

WAYON® is registered trademarks of Wayon Corporation.

Disclaimer

WAYON reserves the right to make changes without further notice to any Products herein to improve reliability, function, or design. The Products are not designed for use in hostile environments, including, without limitation, aircraft, nuclear power generation, medical appliances, and devices or systems in which malfunction of any Product can reasonably be expected to result in a personal injury. The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. WAYON does not assume any liability for infringement of patents, copyrights, or other intellectual property rights of third parties by or arising from the use of Products or technical information described in this document.