



## SCHOTTKY BARRIER RECTIFIERS

### Features

- 3A Schottky barrier diode
- Schottky barrier rectifier
- Guarding protection
- Low forward voltage
- Reverse energy tested
- High current capability
- Extremely low thermal resistance
- RoHS Compliant
- MSL: Level 1



### Mechanical Data

- Case: SMC(JEDEC DO-214AB),molded plastic body
- Mounting position: any
- Polarity: Color band denotes cathode end

### Absolute Maximum Ratings and Electronics characteristics

Ratings@25°C ambient temperature unless otherwise specified

Parameter	Symbol	WSR4003C	WSR6003C	WSR10003C	WSR15003C	WSR20003C	UNITS
Maximum repetitive peak reverse voltage	$V_{RRM}$	40	60	100	150	200	V
Maximum RMS voltage	$V_{RMS}$	28	42	70	105	140	V
Maximum DC blocking voltage	$V_{DC}$	40	60	100	150	200	V
Maximum average forward rectified current	$I_{F(AV)}$	3.0					A
Peak forward surge current 8.3ms single half-sine-wave	$I_{FSM}$	70					A
Maximum instantaneous forward voltage at $I_F=3.0A$	$V_F$	0.55	0.7	0.85	0.95		V
Maximum DC reverse current ( $T_a=25^\circ C$ ) At rated DC blocking voltage ( $T_a=100^\circ C$ )	$I_R$	0.5 20		0.1 10			mA
Typical thermal resistance(junction to ambient)	$R_{\theta JA}$	50					$^\circ C/W$
Operating temperature range	$T_J$	-55 ~ +125					$^\circ C$
Storage temperature range	$T_{STG}$	-55 ~ +150					$^\circ C$

Typical characteristics (Ta=25°C, unless otherwise noted)

Fig. 1 - PEAK FORWARD SURGE CURRENT




Fig. 2 - FORWARD CURRENT DERATING CURVE




Fig.3: Typical Forward Characteristic






Fig.4- Typical Transient Thermal Impedance



Note: The above typical parameters or typical characteristics are only indicative and do not make specific guarantees. If detailed values are required, additional communication and provision are required.


Outline Drawing

Ref. (mm)	Millimeters	
	Min.	Max.
A	1.990	2.700
A1	-	0.300
B	2.750	3.270
E	6.500	7.110
E1	7.600	8.130
D	5.590	6.220
L	0.760	1.600



Recommended Solder Pad Layout

DIM(mm)	MILLIMETERS
A	4.20
B	3.30
C	2.40



Marking Code

Part Number	WSR4003C	WSR6003C	WSR10003C	WSR15003C	WSR20003C
Marking Code	SS34	SS36	SS310	SS315	SS320


Package Information

**Tape & Reel:** 3000 pcs.


Tape and Reel Information

RD	Reel Dimensions	13 inch
W	Overall width of the carrier tape	16 mm
P1	Pitch between successive cavity centers	8 mm


Reel Dimensions Schematic diagram



Tape Dimensions Schematic diagram



Quadrant Assignments for PIN1 Orientation in tape



### Contact Information

No.1001, Shiwan(7) Road, Pudong District, Shanghai, P.R.China.201207

Tel: 86-21-50310888 Fax: 86-21-50757680 Email: market@way-on.com

WAYON website: <http://www.way-on.com>

For additional information, please contact your local Sales Representative.

**WAYON**® is registered trademarks of Wayon Corporation.

---

## Product Specification Statement

The product specification aims to provide users with a reference regarding various product parameters, performance, and usage. It presents certain aspects of the product's performance in graphical form and is intended solely for users to select product and make product comparisons, enabling users to better understand and evaluate the characteristics and advantages of the product. It does not constitute any commitment, warranty, or guarantee.

The product parameters described in the product specification are numerical values, characteristics, and functions obtained through actual testing or theoretical calculations of the product in an independent or ideal state. Due to the complexity of product applications and variations in test conditions and equipment, there may be slight fluctuations in parameter test values. WAYON shall not guarantee that the actual performance of the product when installed in the customer's system or equipment will be entirely consistent with the product specification, especially concerning dynamic parameters. It is recommended that users consult with professionals for product selection and system design. Users should also thoroughly validate and assess whether the actual parameters and performance when installed in their respective systems or equipment meet their requirements or expectations. Additionally, users should exercise caution in verifying product compatibility issues, and WAYON assumes no responsibility for the application of the product.

WAYON strives to provide accurate and up-to-date information to the best of our ability. However, due to technical, human, or other reasons, WAYON cannot guarantee that the information provided in the product specification is entirely accurate and error-free. WAYON shall not be held responsible for any losses or damages resulting from the use or reliance on any information in these product specifications. WAYON reserves the right to revise or update the product specification and the products at any time without prior notice, and the user's continued use of the product specification is considered an acceptance of these revisions and updates. Prior to purchasing and using the product, users should verify the above information with WAYON to ensure that the product specification is the most current, effective, and complete. If users are particularly concerned about product parameters, please consult WAYON in detail or request relevant product test reports. Any data not explicitly mentioned in the product specification shall be subject to separate agreement.

Users are advised to pay attention to the parameter limit values specified in the product specification and maintain a certain margin in design or application to ensure that the product does not exceed the parameter limit values defined in the product specification. This precaution should be taken to avoid exceeding one or more of the limit values, which may result in permanent irreversible damage to the product, ultimately affecting the quality and reliability of the system or equipment.

The design of the product is intended to meet civilian needs and is not guaranteed for use in harsh environments or precision equipment. It is not recommended for use in systems or equipment such as medical devices, aircraft, nuclear power, and similar systems, where failures in these systems or equipment could reasonably be expected to result in personal injury. WAYON shall assume no responsibility for any consequences resulting from such usage.

Users should also comply with relevant laws, regulations, policies, and standards when using the product specification. Users are responsible for the risks and liabilities arising from the use of the product specification and must ensure that it is not used for illegal purposes. Additionally, users should respect the intellectual property rights related to the product specification and refrain from infringing upon any third-party legal rights. WAYON shall assume no responsibility for any disputes or controversies arising from the above-mentioned issues in any form.